

Table Top Dental Autoclave

- Gasket: made of joint less silicon rubber
- Exhaust pressure: manual through the exhaust valve
- Sterilizing pressure: 1.2 to 1.5 kgf/cm² (15 to 20 psi) at 121C.
- Operating pressure: from 15 psi to 20 psi
- Pressure gauge: 0.2.1 kgf/cm² (30 psi)
- Tubular stand and supporting ring: made of mild steel or stainless steel.

INCLUDING:

- Vacuum Breaker
- Tray
- Water level indicator
- Fully automatic PID Purging System



About:

Table Top Dental Autoclave



- All body made of stainless steel.
- The inner/outer chamber & boiler are made of heavy gauge S S with leak proof argon ARC welding.
- The space between the outer chamber is filled with wool to minimize thermal losses.
- Hydraulically tested to withstand 2.5 times the working pressure.
- Steam boiler is fitted with water level indicator, pressure gauge, low water cut off device.
- This afford complete safety to the working personnel against explosi -ve opening.
- An automatic vacuum breaker is fitted to all units as a standard accessory in order to break vacuum in case of steam condensation.
- The flanged immersion type heating element made from very high grade material provides fast formation of pressure in the system & are protected through a electric low water cut off device.
- The chamber is fitted with spring loaded safety valve & a dead weight release valve.
- Sterilization temperature : 120 C, 135 C.
- Suitable to work on 230 volts, single phase and 50Hz AC supply.

Technical Specification: Table Top Dental Autoclave



Dimension (inch)	12X12	12X15
Inner Dimension	300X300	300X375
Capacity	20 liters	25 liters
Heater Load	2 kw	2 kw

CONTACT:



Plot No. 6 - Ekta Vihar, Ambala Cantt.133001



Mobile No.: 8295732110, 7056732110



Sales@labsolutionindia.com



Labsolutionindia.com



GeM
Government
e Marketplace
OEM Regd



MSME
MICRO, SMALL & MEDIUM ENTERPRISES
सूक्ष्म, लघु एवं मध्यम उद्यम